



PYKNOMETERS VF2097, VF2098, VF2099, VF2100

DATASHEET

PRODUCT DESCRIPTION

Specific Gravity Cup for determining the specific gravity or density (or weight per gallon wpg) of coatings, pastes or similar liquids.

Density is defined as weight per unit volume at a specified temperature. Specific Gravity Cups (or Pyknometers) are available in anodised aluminium and stainless steel, 100 ml. and 50 ml.



BUSINESS

Protective Coatings, Corrosion Control, Coating Laboratories, Paint Production, Surface Finishing, Powder Coating, Decorative Coatings, Building Maintenance

STANDARDS

ISO 2811, DIN 53 217, ASTM D 1475

FEATURES

- Available in aluminium en stainless steel
- Available in 100 ml and 50ml
- Including calibration certificate

SCOPE OF SUPPLY

- TQC Pyknometer
- Calibration certificate

ORDERING INFORMATION

VF2098 50 ml Aluminium +/- 61 g VF2097 100 ml Aluminium +/- 70 g VF2100 50 ml Stainless steel +/- 146 g VF2099 100 ml Stainless steel +/- 198 g

USE

- Weigh cleaned density cup empty and record weight
- Temper density cup and test liquid (20°C +-0.5°C; 68°F+-1.0°F)
- Fill density cup
- Put cover on without tilting
- Avoid air bubbles
- Remove overflowing liquid carefully with absorbent cloth
- Weigh filled density cup

 TQC B.V.
 2908 LL Capelle aan den IJssel
 phone: +31 (0)10-7900100
 e-mail: info@tqc.eu

 Molenbaan 19
 The Netherlands
 fax: +31 (0)10-7900129
 www.tqc.eu





Calculate density: Density = weight of filled cup (g) - weight of empty cup (g) ./. Volume of density cup (ml)

SPECIAL CARE

- Always clean the instrument after use.
- Clean the instrument using a soft dry cloth. Never clean the instrument by any mechanical means such as a wire brush or abrasive paper. This may cause, just like the use of aggressive cleaning agents, permanent
- We recommend annual calibration

DISCLAIMER

The right of technical modifications is reserved.

The information given in this sheet is not intended to be exhaustive and any person using the product for any purpose other than that specifically recommended in this sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at his own risk. Whilst we endeavour to ensure that all advice we give about the product (whether in this sheet or otherwise) is correct we have no control over either the quality or condition of the product or the many factors affecting the use and application of the product. Therefore, unless we specifically agree in writing to do so, we do not accept any liability whatsoever or howsoever arising for the performance of the product or for any loss or damage (other than death or personal injury resulting from our negligence) arising out of the use of the product. The information contained in this sheet is liable to modification from time to time in the light of experience and our policy of continuous product development.

fax: